

INTRODUCING . . . THE FT-980 CAT SYSTEM!!!



Join the computer revolution in Amateur Radio with the Computer Aided Transceiver ... the new FT-980 from Yaesu Electronics!

- · 8-Bit microprocessor for greater operating flexibility.
- High-voltage, all solid state transmitter PA for excellent linearity.
- Keyboard entry of frequencies into any of twelve independent VFO/memory registers.
- Amateur band transmit plus general coverage receive capability.
- Full CW break-in with quiet solid state switching.
- CW Spot switch on front panel.
- Digital frequency display with resolution to 10 Hz. Digital readerboard-type coarse frequency sub-display.
- Keyboard entry of sub-bands for Novice, General, or Advanced Class operators. Separate sub-bands may be programmed on each memory.
- Up/Down scanning plus instant ±5 kHz/step QSY from front panel.
- SSB/CW/AM/FSK/FM operation built in. CW and AM Wide/ Narrow selection using optional filters.
- Wide dynamic range and noise floor maintenance provided by husky front end design and IF filter gain balancing.
- 10 Hz synthesizer steps. Quick frequency change via keyboard or scanning controls.
- IF Notch filter at 455 kHz for interference rejection.

- · Audio Peak Filter for narrow band CW signal enhancement.
- RX Audio Tone Control for signal laundering in AF line.
- Variable IF Bandwidth and IF Shift using cascaded filters.
- Memory storage of both frequency and operating mode.
- Pushbutton Memory Check feature for verification of memory frequencies without actually changing operating frequency in use
- Pushbutton Offset Check feature for verification of memory-to-VFO frequency difference.
- · Variable Pulse Width Noise Blanker
- IF Monitor with front panel volume control.
- RF Speech Processor.
- Dual metering of Vcc, Ic. ALC, Compression, Discriminator Center, Relative PO, and SWR (Calibrated).
- Selectable AGC: Slow/Fast/Off.
- Separate RX-only antenna jack.
- . Three FSK shifts built in.
- Optional Electronic Keyer Modu e.
- Optimization of audio passband for mode in use, for preservation of noise figure with changing bandwidth.
- Computer interface optional module available mid-1983, for remote transceiver control from personal computer terminal.

For a detailed brochure covering the FT-980 CAT System, call or write your Authorized Yaesu Dealer.

Price And Specifications Subject To Change Without Notice Or Obligation





0183R